

Programmable Indicator



Ajinkya Programmable Indicator is suitable for showing process parameters like Temperature, Flow, pressure, Humidity, Current etc.

The input is from sources like Rtd, Thermocouple or 4-20 mA, 0-10V etc. Retransmission output 4-20mA or 0-10 V is optional. It can be RS485 / Rs232 input as well.

This instrument is useful in all type of industries like : Sugar, Fertilizer, Chemical, cement, Power Plants, Food industries, Pharmaceuticals & other process industries and OEM's. This is manufactured at our state of art manufacturing facility and tested as per various National/International Standards; ensuring reliability, consistency and quality to our valuable customers.

FEATURES

- Microcontroller based Digital Circuitry
- Four digit LED display for parameter indication.
- Display sizes from 0.5: to 1ft. Indoor as well as Outdoor suitable indicators
- Optional 4 digit display for setpoint display.
- Dust proof membrane keypad for programming.
- Display range User settable
- +/- 0.25% of span accuracy
- Input interface : 4-20mA, 0-10V etc.Or Rs232 / Rs485
- High Low relay alarm outputs optional.
- 4-20mA or 0-10V Control output optional (for retransmission).
- RS 485 Modbus for PC or Serial Printer (Optional)
- Engineering unit identification : Printed lable
- Size 96 x 96 mm or 96 x 48. (DIN standard) wall mount
- MS powder coated enclosure
- Software as well as hardware calibration
- **Calibration Certification as per ISO9000 norms.**

OTHER PRODUCTS

- Timer / Counters
- Ratemeters
- Production Analyser (Counter+ Totaliser + Rate meter + Production storage)
- Ampere Hour Meters
- Data Loggers
- Custom Built Control systems
- SCADA Software / SCADA based Systems



Ajinkya Electronic Systems

131, Kakad Ind. Estate, Off L.J.Road, Mahim, Mumbai 400 016, India
Ph: +91 22 2431 2031 Fax: 2432 2320 Email : sales@ajinkya.com

www.ajinkya.com
www.dataloggersindia.com

www.ajinkya.in

www.amperehourmeter.com
www.displaysystemsindia.com

